

Electromagnetic flowmeter ProcessMaster FEP300

Basic Information

- Brand Name: ABB
- Model Number: FEP300



Product Specification

- Accuracy: High
- Communication Protocol: HART, PROFIBUS, FOUNDATION Fieldbus
- Fluid: Gas, Liquid
- Installation Type: In-line, Insertion
- Material: Stainless Steel, Alloy Steel, Titanium
- Measuring Principle: Differential Pressure
- Output Signal: 4-20mA
- Pressure Range: 0-100Bar
- Process Connection: Flange, Thread, Sanitary
- Product Name: ABB Flow Measurement Products
- Product Type: Flow Measurement
- Range: Wide
- Temperature Range: 0-150
- Warranty: 1 Years
- Highlight: **electromagnetic flowmeter processmaster.**

Product Description

The modular design of the ProcessMaster FEP300 standard version offers the industry's widest range of liners electrodes and sizes to meet the needs of even the most demanding process applications in sectors as diverse as chemical, power, oil & gas, pulp & paper and metals & mining.

Available as integral mount design or remote mount design system.

Looking for a electromagnetic flowmeter with enhanced functionality and extended diagnostic functions? Find out more about ProcessMaster [FEP500](#).

Overview

The powerful transmitter is easy to use and provides the output signal that meets the needs.

ProcessMaster FEP300 is a versatile, reasonably priced, most accurate flow meter tailored for all process industry applications. A flowmeter with base functionality, short delivery and a simple and clearly understandable documentation.

Versatile and simple configuration

- Through glass configuration eliminating the need to remove the cover and reducing commissioning time
- Soft key based functionality
- "Easy Set-up" function

State-of-the-art memory technology

- Data storage enables transmitter exchange without the need for reconfiguration

Diagnostics for real-life-situations

- Simplified plant trouble shooting
- Status messages in accordance with NAMUR
- Help texts in LCD display

ScanMaster in situ verification software option

- Allows the customer to perform in situ verification of the flowmeter and the plant

Data

General specifications:

Measuring value error

- Standard 0.4 % of rate, optional 0.2 % of rate

Nominal diameter

- DN 3 to 2000 (1/10 to 80 in.)

Process connection

- Flange in accordance with DIN 2501 / EN 1092-1, ASME B16.5 / B16.47, JIS, AS2129

Nominal pressure

- PN 10 to 100,
- ASME CL 150, 300, 600, 900, 1500, 2500

Lining

- Hard rubber, soft rubber, PTFE, PFA, ETFE

Communication

- HART, PROFIBUS PA, FOUNDATION Fieldbus

Explosion protection approvals

- ATEX, IECEx, FM, cFM, NEPSI, GOST

Special features:

Process diagnosis

- Empty pipe and partially filling detection

Inner training, pre-shipment training, onsite commissioning, onsite training—Focus on detail and complete



Our Clients:



Our Partners:



Eco-Tech  **Eco-Tech Suzhou Limited**



18626217683



Meliss.Zhao@eco-techsz.com



psa-generators.com

Room 101, Building 19, No. 4388 Dong Shan Avenue, Lin hu Town, Wu Zhong District, Suzhou, China zip 215106