261AS Absolute Pressure Transmitter 4-20mA Flush Diaphragm Pressure Transducer

Basic Information

Brand Name: ABBModel Number: 261AS



Product Specification

Customized Support: OEM

Mounting Bracket: 316 Stainless SteelSupply Voltage Effect: 0.005% Span Per Volt

• Output Signal: 4~20mA

Measurement Range: 0.1...0..100MPA

Power Supply: 24VDC
Operating Temperature: 40~85
Electrical Output Signal: DC 0 ... 10

• Highlight: 261AS Absolute Pressure Transmitter,

4mA flush diaphragm pressure transducer, 20mA flush diaphragm pressure transducer



More Images









Product Description

The compact transmitter class for absolute pressure within the 2600T series. The reliable sensing system with the very latest digital technologies, provides a large turndown ratio of up to 20:1.

Overview

The compact, robust transmitter housing is made of 316 stainless steel as a standard. Due to its high corrosion resistance it can be used in a wide variety of process and ambient conditions without any problems.

The user friendly display allows simple and intuitive local transmitter operation. Full device support, including diagnostic / maintenance information is guaranteed via the Device Type Manager software used in either a stand alone or system engineering tool. The tranmsitter provides local zero and span adjustments even without display

Data

Base accuracy: \pm 0.1 %

Span limits: 0.3 to 3000 kPa abs; 2.25 mmHg to 435 psia

Output signal: 4 to 20 mA, HART

Conforms to SIL2 acc. to IEC 61508 / IEC 61511

Full compliance with PED Category III





18626217683



Melisss.Zhao@eco-techsz.com



psa-generators.com

Room 101, Building 19, No. 4388 Dong Shan Avenue, Lin hu Town, Wu Zhong District, Suzhou, China zip 215106