

## Gauge ABB Pressure Transmitter 261GC, 261GG, 261GJ, 261GM, 261GN

Our Product Introduction

for more products please visit us on [psa-generators.com](http://psa-generators.com)

### Basic Information

- Brand Name: ABB
- Model Number: 261GC, 261GG, 261GJ, 261GM, 261GN



### Product Specification

- Customized Support: OEM
- Mounting Bracket: 316 Stainless Steel
- Supply Voltage Effect: 0.005% Span Per Volt
- Output Signal: 4~20mA
- Measurement Range: 0.1...0..100MPa
- Power Supply: 24VDC
- Operating Temperature: 40~85
- Electrical Output Signal: DC 0 ... 10
- Highlight: **ABB Pressure Transmitter 261GC,  
ABB Pressure Transmitter 261GG,  
261GN abb gauge pressure transmitter**



### More Images



### Product Description

#### Gauge pressure transmitter 261GC, 261GG, 261GJ, 261GM, 261GN

The compact transmitter class for gauge pressure and level with frontbonded diaphragms works within a broad selection of variants, options, fill fluids and wetted materials.

#### Overview

The compact, robust transmitter housing is made of 316 stainless steel as a standard. Due to its high corrosion resistance it can be used in a wide variety of process and ambient conditions without any problems.

The user friendly display allows simple and intuitive local transmitter operation. Full device support, including diagnostic / maintenance information is guaranteed via the Device Type Manager software used in either a stand alone or system engineering tool. The transmitter provides local zero and span adjustments even without display.

The wide range of available process connections meets even special industrial requirements:

- Threaded connections: e.g. for the power, pulp/paper, or oil and gas industries
- Flange connections: e.g. for the chemical industry
- Hygienic connections: e.g. for the pharmaceutical or food and beverages industries


#### Data

Our Product Introduction


for more products please visit us on [psa-generators.com](http://psa-generators.com)

Base accuracy:  $\pm 0.1\%$   
Span limits: 6 to 60000 kPa; 24 inH<sub>2</sub>O to 8700 psi  
Output signal: 4 to 20 mA, HART  
Conforms to SIL2 acc. to IEC 61508 / IEC 61511  
Full compliance with PED Category III



 18626217683

 [Meliss.Zhao@eco-techsz.com](mailto:Meliss.Zhao@eco-techsz.com)

 [psa-generators.com](http://psa-generators.com)

Room 101, Building 19, No. 4388 Dong Shan Avenue, Lin hu Town, Wu Zhong District, Suzhou, China zip  
215106