# JIAPENG Air Compressor Booster Pump WWY-10/4-150 Silent Piston Nitrogen Booster Compressor

# **Basic Information**

• Place of Origin: China

Brand Name: Anshan Jiapeng
Certification: CE ISO9001
Model Number: WWY-10/4-150

Minimum Order Quantity:

• Price: \$2000~20000 per set

Packaging Details: Wooden CaseDelivery Time: With in 7 days

• Payment Terms: D/P, T/T, L/C, L/C, D/A, D/P, T/T, Western

Union, MoneyGram

Supply Ability: 500 Sets Per Year



# **Product Specification**

Input Pressure: 0.4 MpaOutLet Pressure: 15 MpaFlow Rate Nm3/h: 10

• Cylinder Diameter: Φ65+Φ36+Φ20 (3 Stages)

Inlet Size: Rc1/2Outlet Size: G5/8

• Size: 1350\*1050\*1100 (mm)

Weight: 410 Kg
 REV R/min: 470
 Application: O2, N2, Ar2

• Highlight: 470 r/min air compressor booster pump,

AR2 air compressor booster pump, silent nitrogen booster compressor

# **Product Description**

JIAPENG WWY-10/4-150 pISTON TYPE oIL FREE Oxygen Booster Supercharger Air compressor O2 High booster for Oxygen filling About shanghai powerbuilder automation technology co.,ltd

We are the authorized distributor of Anshan Jiapeng. We have been engaged in the assembly of PSA nitrogen generators and oxygen generators in our factory for 15 years, providing approximately 400 sets of PSA nitrogen generators and oxygen generators for domestic and international customers each year, including production, and debugging.

In collaboration with Burkert Valves, we have customized our own double-acting pneumatic valve. Through the design of top and middle pressure equalization, and airflow orifice plates, we continuously optimize and reduce the air consumption ratio of the equipment, thus achieving energy savings. The energy consumption ratio of our equipment has reached the highest level in China. And through our patented silencer, our device noise is controlled to less than 55 db.

In terms of process flow, we have cutting, welding, assembly, filling of molecular sieves, automatic rust removal, spraying, and complete procedures and supporting equipment for commissioning.


In the supply chain aspect, we provide first-line brands such as Atlas Copco, Ingersoll Rand, GDK, Liutech, Bolaite, Hanbell, and BK for air compressors, and provide Boly, Atlas Copco, and Liutech refrigerated dryers, as well as Anshan Jiapeng and Anqing Bailian boosters. We can provide supporting equipment and accessories.

Currently, our company's products are aimed at end-users and distributors worldwide. We provide customized remote systems, color customization, display interface customization, and many other OEM services. And we also provide ASME standard equipment and pressure tanks for USA and Australian market.

For specific selection, please contact our customer manager. We hope to become your trusted long-term partner.

#### About Anshan Jiapeng Compressor Co., Ltd

Anshan Jiapeng Compressor Co., Ltd. is located in the southeast of Liaoning Province, located in the steel capital - Anshan, the company was established in June 1998, the registered capital of 5 million yuan, after the reform of the state-owned enterprises, the first production of oil-free gas compressor joint-stock companies, is the earliest domestic production license manufacturers. The company mainly produces 10 series of compressors with more than 100 models of oil-free air, oxygen, nitrogen, argon, helium, carbon dioxide, sulfur hexafluoride and other non-flammable and explosive gases. At the same time, supporting post-treatment equipment, cold and dry machines, filters, gas storage tanks, to provide users with oil-free, water-free, dust-free and sterile purified air. Fat-filling oil-free compressor can change the original old model structure, convenient maintenance, prolong the service life, has won the national patent (patent no. ZL 20112 0053943.2) is the first compressor production license and general machinery GC certification unit, and through the ISO9001-2008 system certification. National quality qualified products. National mechanical and electrical products energy efficiency grade certification, for many years by anshan Industrial and commercial bureau as industry and commerce exempt enterprises, abide by the contract heavy credit enterprise, Anshan technical supervision bureau "anticounterfeiting and fidelity enterprise".



### **Working Principle**

Compression of gas: The air compressor draws in a large volume of air through one or more cylinders and compresses it using a piston or a screw-type compression device. As the gas is compressed, the molecular spacing decreases, resulting in increased gas pressure and temperature.

Discharge of high-pressure gas: After compression, the high-pressure gas is pushed into the air compressor's storage tank or delivery pipelines. The storage tank is used to store the compressed air and balance the supply of air from the compressor.

Control system: Air compressors are typically equipped with a control system to monitor and regulate the gas pressure. When the pressure drops below a set value, the control system starts the compressor to increase the gas supply. When the pressure reaches the preset upper limit, the control system stops or reduces the operation of the compressor.

Cooling system: During the compression process, the temperature of the gas increases. Therefore, air compressors are usually equipped with a cooling system to lower the gas temperature. This can be achieved through air cooling or water cooling.

Lubrication system: To reduce friction and wear, air compressors typically require a lubrication system to provide lubricating oil or lubricants to the compression device and other moving parts.

In summary, an air compressor compresses a large volume of air into high-pressure gas to meet the compressed air requirements in various industrial and commercial applications. The key steps in the working principle include gas compression, discharge of high-pressure gas, control system, cooling system, and lubrication system.

# **Product description**

Lot.	Item	Parameter
1	n ne compression mealum	Oxygen (must be dry and free of particulate gas)
2	Model	WWY-10/4150

3	Flow ra	ate (standard) Nm <sup>3</sup> /h	10
4	Inlet te	emperature	≤40
5	Inlet p	ressure MPa	0.4
6	Outlet	Pressure MPa	15
7	Cylinder diameter quantity		Φ65+Φ36+Φ20 mm
8	Revolving Speed r/min		470
9	Cooling Mode		Air cooling + water cooling (in circulation)
10	Lubrication method		Oil free lubrication
11	Compressed series		Three Level
12	Structural style		Angle type, W type, single unit
		Power kW	5.5
	Motor	The electric system	AC380V, three-phase electricity, 50Hz,
13		Insulation grade	B Grade
		Protection grade	IP44
		Start Mode	Direct Starting
14	Drive Mode		Belt Drive
15	The installation type		The base type
16	Noise Figure dB(A)		≤80
17	Control mode		PLC Touch screen control: maintenance alarm, over temperature alarm, overpressure alarm, motor overload alarm and so on
18	Dimension of inlet and outlet		Rc1/2 Rc5/8
19	Size(L×W×H) mm		1350X1050X1100
20	Weigh	t kg	≈410

# The basic parameters listed in this table can be confirmed according to the actual working conditions

Touch display PLC control

Remote control is optional

Inlet and outlet pressure overload, temperature overheating, cooling water failure, circulation rolling alarm and stop Operation time display, maintenance cycle prompt

With water tank and circulating pump without external pipeline, filling antifreeze at low temperature without obstruction.

# Our Service

- 1. We can provide acceptance video and shipping
- 2. We can provide the boot video and boot introduction
- 3. We can provide maintenance videos and instructions
- 4. For dealers we can provide door-to-door service and factory training in your factory







Melisss.Zhao@eco-techsz.com



psa-generators.com