

JIAPENG SWY-60/4-200 PISTON TYPE Oil Free Supercharger Booster Compressor

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Anshan Jiapeng
- Certification: CE ISO9001
- Model Number: SWY-60/4-200
- Minimum Order Quantity: 1
- Price: \$2000~20000 per set
- Packaging Details: Wooden Case
- Delivery Time: With in 7 days
- Payment Terms: D/P, T/T, L/C, L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 500 Sets Per Year



Product Specification

- Input Pressure: 0.4 Mpa
- OutLet Pressure: 15 Mpa
- Flow Rate Nm3/h: 60
- Cylinder Diameter: 2- Φ 70+ Φ 50+ Φ 30 (3 Stages)
- Inlet Size: Rc1
- Outlet Size: G5/8
- Size: 1450*1100*1250 (mm)
- Weight: 540 Kg
- REV R/min: 640
- Application: O2, N2, Ar2
- Highlight: **15 Mpa oil free booster compressor ,
640 r/min oil free booster compressor ,
piston type booster compressor**

Product Description

JIAPENG SWY-60/4-200 PISTON TYPE oIL FREE Oxygen Booster Supercharger Air compressor O2 High booster for Oxygen filling

About shanghai powerbuilder automation technology co.,Ltd

We are the authorized distributor of Anshan Jiapeng. We have been engaged in the assembly of PSA nitrogen generators and oxygen generators in our factory for 15 years, providing approximately 400 sets of PSA nitrogen generators and oxygen generators for domestic and international customers each year, including production, and debugging.

In collaboration with Burkert Valves, we have customized our own double-acting pneumatic valve. Through the design of top and middle pressure equalization, and airflow orifice plates, we continuously optimize and reduce the air consumption ratio of the equipment, thus achieving energy savings. The energy consumption ratio of our equipment has reached the highest level in China. And through our patented silencer, our device noise is controlled to less than 55 db.

In terms of process flow, we have cutting, welding, assembly, filling of molecular sieves, automatic rust removal, spraying, and complete procedures and supporting equipment for commissioning.

In the supply chain aspect, we provide first-line brands such as Atlas Copco, Ingersoll Rand, GDK, Liutech, Bolaite, Hanbell, and BK for air compressors, and provide Boly, Atlas Copco, and Liutech refrigerated dryers, as well as Anshan Jiapeng and Anqing Bailian boosters.

In addition to the aforementioned offerings, our company excels in delivering comprehensive solutions for PSA Hydrogen Generation Plants. We understand the unique requirements of the buyer's project in Nepal and are committed to providing top-notch products and services.

Our product portfolio includes cutting-edge equipment and accessories that are essential for efficient and reliable hydrogen generation. We offer a wide range of components such as pressure swing adsorption (PSA) units, methanol reformers, purification systems, compressors, storage tanks, and distribution systems. These components are meticulously designed and manufactured to meet the highest industry standards, ensuring optimal performance and safety.

One of our key strengths lies in customization. We recognize that each project may have specific needs and preferences, which is why we offer tailor-made solutions. Our experienced team of engineers works closely with clients to understand their requirements and design bespoke systems that align with their objectives. Whether it's remote system integration, color customization, or display interface modification, we have the expertise to cater to diverse customization needs.

Furthermore, our commitment to quality and compliance is reflected in our adherence to ASME standards. For customers in the USA and Australian markets, we provide equipment and pressure tanks that meet the rigorous requirements of these regions. Our ASME-certified products ensure the highest levels of safety, efficiency, and durability, giving our clients peace of mind.

As a customer-centric organization, we prioritize customer satisfaction and long-term partnerships. We offer comprehensive after-sales support, including installation guidance, training, maintenance, and technical assistance. Our dedicated team is readily available to address any queries or concerns that may arise during the project implementation phase or throughout the lifespan of our products.

With our extensive range of products, customization capabilities, adherence to industry standards, and commitment to customer service, we are confident in our ability to meet the buyer's requirements for the PSA Hydrogen Generation Plant in Nepal.

For specific selection, please contact our customer manager. We hope to become your trusted long-term partner.

About Anshan Jiapeng Compressor Co., Ltd

Anshan Jiapeng Compressor Co., Ltd. is located in the southeast of Liaoning Province, located in the steel capital - Anshan, the company was established in June 1998, the registered capital of 5 million yuan, after the reform of the state-owned enterprises, the first production of oil-free gas compressor joint-stock companies, is the earliest domestic production license manufacturers. The company mainly produces 10 series of compressors with more than 100 models of oil-free air, oxygen, nitrogen, argon, helium, carbon dioxide, sulfur hexafluoride and other non-flammable and explosive gases. At the same time, supporting post-treatment equipment, cold and dry machines, filters, gas storage tanks, to provide users with oil-free, water-free, dust-free and sterile purified air. Fat-filling oil-free compressor can change the original old model structure, convenient maintenance, prolong the service life, has won the national patent (patent no. ZL 20112 0053943.2) is the first compressor production license and general machinery GC certification unit, and through the ISO9001-2008 system certification. National quality qualified products. National mechanical and electrical products energy efficiency grade certification, for many years by anshan Industrial and commercial bureau as industry and commerce exempt enterprises, abide by the contract heavy credit enterprise, Anshan technical supervision bureau "anti-counterfeiting and fidelity enterprise".

Jiapeng booster advantages

- 1.Chinese and English operation interface(pic1)
- 2.With abnormal alarm reminder function(pic2)
3. The filling booster is equipped with a water tank and a water pump.
After 40 liters of water is added to water tank , the booster can work when the power is turned on. There is no need for a extra water tank and pump!



pic1



pic2

Working Principle

Compression of gas: The air compressor draws in a large volume of air through one or more cylinders and compresses it using a piston or a screw-type compression device. As the gas is compressed, the molecular spacing decreases, resulting in increased gas pressure and temperature.

Discharge of high-pressure gas: After compression, the high-pressure gas is pushed into the air compressor's storage tank or delivery pipelines. The storage tank is used to store the compressed air and balance the supply of air from the compressor.

Control system: Air compressors are typically equipped with a control system to monitor and regulate the gas pressure. When the pressure drops below a set value, the control system starts the compressor to increase the gas supply. When the pressure reaches the preset upper limit, the control system stops or reduces the operation of the compressor.

Cooling system: During the compression process, the temperature of the gas increases. Therefore, air compressors are usually equipped with a cooling system to lower the gas temperature. This can be achieved through air cooling or water cooling.

Lubrication system: To reduce friction and wear, air compressors typically require a lubrication system to provide lubricating oil or lubricants to

the compression device and other moving parts.

In summary, an air compressor compresses a large volume of air into high-pressure gas to meet the compressed air requirements in various industrial and commercial applications. The key steps in the working principle include gas compression, discharge of high-pressure gas, control system, cooling system, and lubrication system.

Product description

Lot.	Item		Parameter
1	The compression medium		Oxygen (must be dry and free of particulate gas)
2	Model		SWY-60/4-200
3	Flow rate (standard) Nm ³ /h		60
4	Inlet temperature		≤40
5	Inlet pressure MPa		0.4
6	Outlet Pressure MPa		20
7	Cylinder diameter quantity		2-Φ70+Φ50+Φ30
8	Revolving Speed r/min		640
9	Cooling Mode		Air cooling + water cooling (in circulation)
10	Lubrication method		Oil free lubrication
11	Compressed series		Three Level
12	Structural style		Angle type, W type, single unit
13	Motor	Power kW	22
		The electric system	AC380V, three-phase, 50Hz,
		Insulation grade	B Grade
		Protection grade	IP44
		Start Mode	Direct Starting
14	Drive Mode		Belt Drive
15	The installation type		The base type
16	Noise Figure dB(A)		≤80
17	Control model		PLC Touch screen control: maintenance alarm, over temperature alarm, overpressure alarm, motor overload alarm and so on
18	Dimension of inlet and outlet		Rc1 Rc5/8
19	Size(L×W×H) mm		1450*1100*1250
20	Weight kg		540

The basic parameters listed in this table can be confirmed according to the actual working conditions

Touch display PLC control

Remote control is optional

Inlet and outlet pressure overload, temperature overheating, cooling water failure, circulation rolling alarm and stop

Operation time display, maintenance cycle prompt

With water tank and circulating pump without external pipeline, filling antifreeze at low temperature without obstruction.

Our Service

1. We can provide acceptance video and shipping list
2. We can provide the boot video and boot introduction
3. We can provide maintenance videos and instructions
4. For **dealers** we can provide door-to-door service and factory training in your factory



18626217683



Meliss.Zhao@eco-techsz.com



psa-generators.com

Room 101, Building 19, No. 4388 Dong Shan Avenue, Lin hu Town, Wu Zhong District, Suzhou, China zip
215106